xFitter: Releases and Updates July, 2016

xFitter versions are labeled as xfitter-i.j.k where i is the stable release number, j is beta release number, and k is bug fixes.

		k is bug fixes.
Release	Date	Description
xfitter-1.2.2	8.07.2016	 Fix in profiling due to multiple sign flips, affects also reweighting. Fix in the output of PDFs, strange is symetrised to (s + s̄)/2. Fix in calculation of theory error bands for parametrisation uncertainties for thetherr option. Fix for has_photon LHAPDF variable and protection against LHAPDFQ0 with photon PDFs. Fixes to dipole steering file in input steering file, updated now to current settings. Added the H1 beauty data to the list of data files Fix in the default theoretical parameters for HVQMNR to be used not in Fit mode. Fix on warning message from Fastnlo. Added examples in the example directory together with the tutorial slides from CTEQ 2016 school. Fix in configuration fordisable-root option. Fix in ρhoton PDF sum rules.
Release	Date	Description
xfitter-1.2.1	11.05.2016	 Update the EW corrections in CMS 7 TeV jet data, as used for the publication. Fix in the Hessian error for external codes: FONLL schemes, DGLAP_QED and DGLAP_APFEL_QED were affected. Fix in α_s for running mass option in FONLL. Fix in the cached PDFs when using Hessian errors. Fix in the LHAPDF errors for the MNR code. Allow the FF scheme for the MNR calculations. Fix in the handling of the virual grids (hyperbins were not filled). Improved warning messages in FastNLO from the photon PDF.

Release	Date	Description
xfitter-1.2.0	15.02.2016	 Project renamed from herafitter to xfitter. Added stand-alone scripts for downloading data/theory files: getter . No need of theory directory anylonger, the theory files are now stored under same location with data files. Change in the executable names: FitPDF → xfitter DrawPdfs → xfitter-draw postproc → xfitter-process
		 Updated configure.ac to work with latest QCDNUM which is now available with autotools installation (> 17.01.10). new QCDNUM allows possibility to have more than standard PDFs.
		 Added QED PDFs via generalised nxn convolution engines of QCDNUM. Added interface to APFEL which provides access to: evolution code: added DGLAP_APFEL option for standard evolution, or DGLAP_APFEL_QED for QED adjusted evolution. FONLL heavy flavour schemes with multiple options.
		 Added interface to n-space code MELA for Mellin Transformation and it is available via configuration flag. Added direct access to LHAPDFs avoiding QCDNUM: LHAPDFNATIVE option Added more data formatted for xfitter: updated Tevatron data, LHCb, HERA)
		 Addeddisable-root option (root is enabled by default). Default steering updated to HERAI+II data. Removed DrawResults package, which was redundant, and added and updated drawing options for data files. Added fixes to DIS electroweak part of the code. Fixed several fortran warning messages.
		• Unifying theory interface for expression between FastNLO and APPLGRID usage.
Release xfitter-1.2.0	Date 15.02.2016	 Description Updated FastNLO to the latest version Installation possible withprefix option, added xfitter-config script. Added MNR calculation code as used for the LHCb and HERA data analysis [Eur.Phys.J. C75 (2015) 8, 396] Added new options for the reweighting using Giele-Keller weights. Merged common codes between profiling and reweighting. Fixing lapack and blas tests to give configure errors and stop Updated the ABM calculations in sync with OPENQCDRAD 2.0b4 Added possibility to get integrated cross sections for DIS. Tools/RunJobs and steerings for diffraction adjusted to xFitter.

-		
Release	Date	Description
herafitter-1.1.1	3.03.2015	 Fix in the reweighting code in the new interface to LHAPDFv6 involving the gluon ID (different gluon ID is used between LHAPDFv5 and v6) Fix in TMD code: remove the CERNLIB dependence and update to LHAPDFv6, fix to the treatment of heavy quarks; updated steering files and README. Fix of the TheoryType expression parsing used in data files Fix in transformation from a Hessian to MC PDF set to preserve correlations Fixed/improved the dynamic memory allocation for systematic arrays NSysMax and WORK arrays. Fix of the warning for treatment of statistical errors (when default treatment changed to poisson errors). Fix in the χ² code using additional rescale of stat. uncertainty to account for systematic shifts Fixed/added drawing options for Diffractive PDFs. Added F₂ structure function in reaction type instead of cross section.
Release	Date	Description
herafitter-1.1.0	29.09.2014	 Removed dependence on CERNLIB and related libraries. Added interface to LHAPDFv6. Added more and improved drawing options for visualisation of results. Added possibility to deal with multi-dimensional data (virtual grids). Additional options in parametrisation styles: added mixed forms between HERA style for gluon and sea and CTEQ style for valence. Added new data from Tevatron, ATLAS and CMS. Added improvements and more flexibility in the χ² and covariance matrix code: possibility to transform into nuisance representation for data with uncertainties given in the covariance form. Included a new fastNLO version, which was generalised in order to accommodate DiffTop grids. Added DiffTop grids via fastNLO.

Release	Date	Description
herafitter-1.0.0	10.12.2013	 Added possibility to change the name of the output directory in steering.txt Added a dummy reaction type for testing data formats. Centralised implementation of the scale variations for the DIS processes. Enabled possibility to perform LO PDF fits. Added possibility to determine generalised minima based on multiple sampling of minuit files. Improved quantitative comparison of data to predictions by adding: Possibility to include PDF uncertainties in the χ² evaluation; Possibility to use external predictions as text les (similar format style as for data) in the χ² evaluation;
		 Added more options for χ² representation: Use of covariance and/or correlation matrix (statistical or systematic); Use of parabolic approximation for asymmetric uncertainties.
		 Considerable improvements in the drawing tools: Added new executable to draw PDFs: DrawPdfs; Added possibility of multiple overlays, each PDF can be plotted separately; Possibility to visualise the pulls (only for data sets that provide bin ranges).
		 Possibility to fit Lead PDF; Improved interface to Transverse Momentum Distributions (TMDs): Evolution is fully integrated into HERAFitter; Evolution of valence quarks is also included; Calculation of the longitudinal cross-section is also included;
		 Simplified interface to the parametrisation style; Fixes to the LHAPDF reweighted PDFs due to random seed generator causing large fluctuations. New generalised APPLGRID interface: Added parser to identify theory expressions; Added possibility to select the values for the CKM matrix elements from APPLGRID or HERAFitter. Added possibility to flag a data bin to be excluded from the fit.
		• Tool to convert covariance matrix to nuisance parameter representation.

Release	Date	Description
herafitter-0.3.1	11.06.2013	 Fixing interface with LHAPDF when fitting only α_S Fixing the floating point error for negative predictions in χ² calculation
		• Fixing the treatment of the statistical correlations
		• Fixing treatment for asymmetric uncertainties
herafitter-0.3.0	26.03.2013	• The theoryfiles directory is detached from the release (to be downloaded separately)
		• Added via automake tools a make check to test sanity of the codes.
		• Added a User Example directory for reference outputs.
		• Inclusion of more data sets (like CMS, Tevatron).
		• Implemented a treatment for asymmetric systematic uncertainties.
		• Added updates to ACOT code which include higher order contributions for F_2 and F_L .
		• Added new dipole models.
		• Implementation of treatment for the unintegrated PDFs (or TMDs).
		• Reorganisation of the χ^2 module, the old style is preserved and it should be used for the offset method and covariance matrix for chisquare representation.
		• Implementation of PDF reweighting based on eigenvectors.
		• Added new parametrisation styles and regularisation techniques.
		• A New FastNLO format was introduced.

Release	Date	Description
herafitter-0.2.1	13.07.2012	• Fixing the RT Fast scheme: the k-factors were determined for single point instead for each data point which is now fixed.
herafitter-0.2.0	9.05.2012	 New implementation of RT scheme (VFNS): Standard and Optimal NLO and NNLO. New module for heavy flavour treatment using VFNS ACOT scheme using k-factor technique. Different variants of ACOT scheme available, as well as ZM-VFNS. New module for heavy flavour treatment using FFNS ABM scheme. New module for DIPOLE models (GBW, IIM). New Hathor module for tt cross section calculation - optional via configure flag. New Diffractive module for fits to diffractive data. New data sets from HERA, Fixed target experiments, Tevatron and LHC. New interface to LHAPDF to access external PDFs for prediction estimation - optional via configure flag. New module for NNPDF reweighting tool - optional via configure flag. New addition for error handling providing a summary of errors. Improved interface to FASTNLO module via FASTNLOREADER. Improved interfaces between QCDNUM and cross-section calculation codes. PDF caching mechanisms for faster computations. Improved modularity of the structure by separating the chisquare definition from minimisation routine. New common interfaces to access PDFs and alphas, in interface/src . Improved handling of PDF parametrisation, in src/pdf-param.f . Centralised passing of the constants to EW module via ewparam.txt card. New implementation for scale variation for APPLGRID and FASTNLO via steering.txt card
herafitter-0.1.0	15.09.2011	• Initial release